[32] M. Myślak and D. Deja. Developing game-structure sensitive matchmaking system for massive-multiplayer online games. In *Social Informatics*, pages 200–208. Springer, 2014.

[33] T.-H. D. Nguyen, Z. Chen, and M. S. El-Nasr. *Analytics-based AI Techniques for Better Gaming Experience*, volume 2 of *Game AI Pro*. CRC Press, Boca Raton, Florida, 2015.

[34] S. Ólafsson. Weighted matching in chess tournaments. *Journal of the Operational Research Society*, 41(1):17–24, 1990.

[35] C. N. Osiakwan and S. G. Akl. The maximum weight perfect matching problem for complete weighted graphs is in PC. In *Proceedings of the Second IEEE Symposium on Parallel and Distributed Processing*, pages 880–887. IEEE, 1990.

[36] E. A. Riskin, R. Ladner, R.-Y. Wang, and L. E. Atlas. Index assignment for progressive transmission of full-search vector quantization. *IEEE Transactions on Image Processing*, 3(3):307–312, 1994.

[37] J. Runge, P. Gao, F. Garcin, and B. Faltings. Churn prediction for high-value players in casual social games. In *IEEE Conference on Computational Intelligence and Games*, pages 1–8. IEEE, 2014.

[38] M. Stanescu. Rating systems with multiple factors. In *Master Thesis*. School of Informatics, University of Edinburgh, 2011.

[39] SuperData. eSports market brief: US accounts for almost half of total viewership. `https://www.superdatares earch.com/blog/esports-brief/`. Online; accessed Mar, 2016.

[40] M. Suznjevic, M. Matijasevic, and J. Konfic. Application context based algorithm for player skill evaluation in MOBA games. In *International Workshop on Network and Systems Support for Games (NetGames)*, pages 1–6. IEEE, 2015.

[41] P. Tassi. Riot's 'League of Legends' reveals astonishing 27 million daily players, 67 million monthly. `http://www.forbes.com/sites/insertcoin/2014/01/27/riots-league-of-legends-reveals-astonishing-27-million-daily-players-67-million-monthly/#26ff8e543511`. Online; accessed May, 2016.

[42] J. van Rantwijk. Maximum Weighted Matching. `http://jorisvr.nl/article/maximum-matching`. Online; accessed May, 2016.

[43] B. G. Weber, M. John, M. Mateas, and A. Jhala. Modeling player retention in Madden NFL 11. In *Innovative Applications of Artificial Intelligence (IAAI)*, 2011.

[44] D. B. West. *Introduction to graph theory*. Prentice Hall, 2001.

[45] G. Yannakakis, P. Spronck, D. Loiacono, and E. André. Player modeling. In *Artificial and Computational Intelligence in Games*, pages 45–59. 2013.

[46] S. Yoon, J. Koehler, and A. Ghobarah. Prediction of advertiser churn for Google AdWords. In *the Joint Statistical Meetings (JSM) Proceedings*, 2010.