

8. REFERENCES

- [1] G. Asharov and Y. Lindell. A full proof of the BGW protocol for perfectly secure multiparty computation. *J. Cryptology*, 30(1):58–151, 2017.
- [2] G. Asharov, Y. Lindell, T. Schneider, and M. Zohner. More efficient oblivious transfer and extensions for faster secure computation. In *Conference on Computer and Communications Security*, pages 535–548, 2013.
- [3] M. Ben-Or, S. Goldwasser, and A. Wigderson. Completeness theorems for non-cryptographic fault-tolerant distributed computation. In *STOC*, pages 1–10, 1988.
- [4] P. Boldi and S. Vigna. Axioms for centrality. *Internet Mathematics*, 10(3-4):222–262, 2014.
- [5] S. Brin and L. Page. The anatomy of a large-scale hypertextual web search engine. *Computer Networks*, 30(1-7):107–117, 1998.
- [6] M. Burkhart, M. Strasser, D. Many, and X. A. Dimitropoulos. SEPIA: privacy-preserving aggregation of multi-domain network events and statistics. In *USENIX*, pages 223–240, 2010.
- [7] R. Canetti. Security and composition of multiparty cryptographic protocols. *J. Cryptology*, 13(1):143–202, 2000.
- [8] D. Chaum, C. Crépeau, and I. Damgård. Multiparty unconditionally secure protocols. In *STOC*, pages 11–19, 1988.
- [9] M. De Domenico, A. Solé-Ribalta, S. Gómez, and A. Arenas. Navigability of interconnected networks under random failures. *Proceedings of the National Academy of Sciences*, 111(23):8351–8356, 2014.
- [10] D. Demmler, T. Schneider, and M. Zohner. Ad-hoc secure two-party computation on mobile devices using hardware tokens. In *USENIX Security Symposium*, pages 893–908, 2014.
- [11] K. C. Foster, S. Q. Muth, J. J. Potterat, and R. B. Rothenberg. A faster katz status score algorithm. *Computational & Mathematical Organization Theory*, 7(4):275–285, 2001.
- [12] R. Gennaro, M. O. Rabin, and T. Rabin. Simplified VSS and fact-track multiparty computations with applications to threshold cryptography. In *PODC*, pages 101–111, 1998.
- [13] O. Goldreich. *The Foundations of Cryptography - Volume 2, Basic Applications*. Cambridge University Press, 2004.
- [14] O. Goldreich, S. Micali, and A. Wigderson. How to play any mental game or A completeness theorem for protocols with honest majority. In *STOC*, pages 218–229, 1987.
- [15] S. Goldwasser and S. Micali. Probabilistic encryption. *J. Comput. Syst. Sci.*, 28(2):270–299, 1984.
- [16] S. Goldwasser, S. Micali, and C. Rackoff. The knowledge complexity of interactive proof systems. *SIAM J. Comput.*, 18(1):186–208, 1989.
- [17] A. Halu, R. J. Mondragón, P. Panzarasa, and G. Bianconi. Multiplex pagerank. *PLoS one*, 8(10):e78293, 2013.
- [18] M. Kantarcioglu and C. Clifton. Privacy-preserving distributed mining of association rules on horizontally partitioned data. *Transactions on Knowledge and Data Engineering*, 16(9):1026–1037, 2004.
- [19] L. Katz. A new status index derived from sociometric index. *Psychometrika*, pages 39–43, 1953.
- [20] M. Kivelä, A. Arenas, M. Barthelemy, J. P. Gleeson, Y. Moreno, and M. A. Porter. Multilayer networks. *Journal of Complex Networks*, 2(3):203–271, 2014.
- [21] N. Korula and S. Lattanzi. An efficient reconciliation algorithm for social networks. *PVLDB*, 7(5):377–388, 2014.
- [22] D. Liben-Nowell and J. M. Kleinberg. The link prediction problem for social networks. In *CIKM*, pages 556–559, 2003.
- [23] X. Lin, C. Clifton, and M. Zhu. Privacy-preserving clustering with distributed EM mixture modeling. *Knowl. Inf. Syst.*, 8(1):68–81, 2005.
- [24] Y. Lindell and B. Pinkas. Privacy preserving data mining. In *Crypto*, pages 36–54, 2000.
- [25] Y. Lindell and B. Pinkas. A proof of security of yao’s protocol for two-party computation. *J. Cryptology*, 22(2):161–188, 2009.
- [26] Z. Lu, B. Savas, W. Tang, and I. S. Dhillon. Supervised link prediction using multiple sources. In *ICDM*, pages 923–928, 2010.
- [27] D. Malkhi, N. Nisan, B. Pinkas, and Y. Sella. Fairplay - secure two-party computation system. In *USENIX Security Symposium*, pages 287–302, 2004.
- [28] M. J. Rattigan and D. Jensen. The case for anomalous link discovery. *SIGKDD Explor. Newsl.*, 7(2):41–47, 2005.
- [29] P. Sarkar and A. W. Moore. A tractable approach to finding closest truncated-commute-time neighbors in large graphs. In *UAI*, pages 335–343, 2007.
- [30] A. Shamir. How to share a secret. *Commun. ACM*, 22(11):612–613, 1979.
- [31] A. Solé-Ribalta, M. De Domenico, S. Gómez, and A. Arenas. Centrality rankings in multiplex networks. In *WebSci*, pages 149–155, 2014.
- [32] D. R. Stinson. *Cryptography - theory and practice*. Discrete mathematics and its applications series. Chapman & Hall/CRC, 2006.
- [33] T. Tassa. Secure mining of association rules in horizontally distributed databases. *Transactions on Knowledge and Data Engineering*, 26(4):970–983, 2014.
- [34] J. Vaidya and C. Clifton. Privacy preserving association rule mining in vertically partitioned data. In *KDD*, pages 639–644, 2002.
- [35] C. Wang, V. Satuluri, and S. Parthasarathy. Local probabilistic models for link prediction. In *ICDM*, pages 322–331, 2007.
- [36] A. Yao. Protocols for secure computation. In *FOCS*, pages 160–164, 1982.
- [37] A. C. Yao. How to generate and exchange secrets. In *FOCS*, pages 162–167, 1986.
- [38] J. Zhan, S. Matwin, and L. Chang. Privacy preserving collaborative association rule mining. In *Data and Applications Security*, pages 153–165, 2005.